

# Nosler BST 150 gr



Bullet type	Bullet weight	Ballistic coefficient	Product number
Nosler Ballistic Tip)	9.7 g / 150 gr	0.435	20176252

Velocity			
V <sub>0</sub>	V <sub>100</sub>	V <sub>200</sub>	V <sub>300</sub>
860 (m/s) / 2822 (f/s)	790 (m/s) / 2612 (f/s)	724 (m/s) / 2412 (f/s)	661 / 2221 (f/s)

Energy			
E <sub>0</sub>	E <sub>100</sub>	E <sub>200</sub>	E <sub>300</sub>
3596 (J) / 2653 (ft.-lb.)	3037 (J) / 2274 (ft.-lb.)	2549 (J) / 1939 (ft.-lb.)	2124 (J) / 1644 (ft.-lb.)

Zero range, meters	Height of trajectory above line of sight if sighted in at X meter. For sights 40mm above bore					
	50	80	100	150	200	300 m
80	-5	999	-5	-44	-127	-437
100	-2	4	999	-37	-118	-423
150	11	24	25	999	-68	-348
200	27	51	59	51	999	-246

Sighting distance in yards	Height of trajectory above line of sight if sighted in at X yards. For sights 1,6 inch above bore				
	50	100	150	200	300 yds
50	999	0.4	-0.4	-2.7	-11.7
100	-0.2	999	-1.1	-3.5	-13

<b>150</b>	0.1	0.7	999	-2.1	-10.9
<b>200</b>	0.7	1.8	1.6	999	-7.7

Winddrift in mm for a 5 m/s cross wind		
<b>100</b>	<b>200</b>	<b>300 m</b>
25	105	246

Winddrift in inches for a 10 m.p.h cross wind		
<b>100</b>	<b>200</b>	<b>300 yds</b>
0.7	3.1	7.2

**NORMA PRECISION AB**  
670 40 Åmotfors Sweden



products an extra shine.

**Royal Purveyor** Norma has been an official purveyor to the Royal Court for many years, which gives the



**Intertek**

**Together ahead. RUAG**