

HUNTING FMJ AND CARBON ARROW SELECTION CHART

COMPOUND BOW	YOUR ARROW LENGTH										RECURVE	LONGBOW	
BOW RATING TO 301-340 FPS	23"	24"	25"	26"	27"	28"	29"	30"	31"	32"			
BOW POUNDAGE												BOW POUNDAGE	
22-26				700, 600	700, 600	600	600	600	500, 480, 470, 460	500, 480, 470, 460		38-43	
27-31			700, 600	700, 600	600	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5		44-49	
32-36		700, 600	700, 600	600	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	32-36	50-55	
37-41	700, 600	700, 600	600	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	37-41	56-61	
42-46	700, 600	600	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	42-46	62-67	
47-51	600	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	47-51	68-73	
52-56	600	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	52-56	74-79	
57-61	600	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	300, 280, 260, 250, 240, T64 - 7.9	57-61	80-85	
62-66	500, 480, 470, 460	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	300, 280, 260, 250, 240, T64 - 7.9	260, 250, 240	62-66		
67-72	500, 480, 470, 460	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	300, 280, 260, 250, 240, T64 - 7.9	260, 250, 240				
73-78	400, 390, T64 - 9.5	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	300, 280, 260, 250, 240, T64 - 7.9	260, 250, 240					
79-84	400, 390, T64 - 9.5	400, 390, T64 - 9.5	340, 330, 320, T64 - 7.9	340, 330, 320, 300, T64 - 7.9	330, 320, 300, T64 - 7.9	300, 280, 260, 250, 240, T64 - 7.9	260, 250, 240						

NOTE: For fractional arrow lengths round up or down to closest column. Examples, of an arrow length is 28.25 round down to the 28" column. If arrow length is 28.5 round up the the 29" column.

T64 Selection Chart Key

Size	Part Number
T64 DF - 9.5	228729
T64 DF - 7.9	428728

ADJUSTING THE CHART TO YOUR BOW SET-UP

The hunting chart is based on a Bow Speed Rating of 301-340 FPS and 100 -grain points. If your set-up is different, make the following adjustment to your bow weight.

Bow Speed Ratings:		Point Weights	
Up to 300 FPS	subtract 5 lbs of bow weight	75 grains	subtract 3 lbs of bow weight
301-340 FPS	no adjustment	100 grains	no adjustment
341-350 FPS	add 5 lbs of bow weight	125 grains	add 3 lbs of bow weight
351 FPS or higher	add 10 lbs of bow weight	150 grains	add 6 lbs of bow weight